

Your Global Automation Partner

TURCK

Connectivity In-Stock Program



TURCK THE SOLUTION PROVIDER

85,000+ SOLUTIONS

Pioneer in non-contact
sensing technology

Developed innovative **connectivity**
solutions in response to our sensor customer needs

Recognized need and advanced knowledge of harsh duty
environments lead to **I/O solutions**

28 GLOBAL
SUBSIDIARIES

with **PARTNERS** in
60 FURTHER
COUNTRIES




more than
2,000 EXPERIENCED
SALES REPRESENTATIVES

**SUPPORT &
DEDICATED SERVICE**

50 YEARS OF EXPERIENCE 2014 2013 2012 2011

LIFETIME WARRANTY

RESPOND
and SOLVE over **1,200** inquiries
per day

 **3,500+**
APPLICATION ENGINEERS

www.
turck
.com

TABLE OF CONTENTS

| | |
|---------------------------|-----------|
| Introduction | 4 |
| M8 Picofast | 5 |
| M12 Eurofast | 7 |
| 7/8" Minifast | 14 |
| M12 Junction Boxes | 18 |
| M23 Multifast | 19 |
| Splitters | 20 |
| Ethernet | 21 |
| DeviceNet | 23 |
| Valve Plugs | 25 |
| A-Size Powerfast | 28 |
| D-Size Powerfast | 30 |

CONNECTIVITY IN-STOCK PROGRAM

At Turck, we have long prided ourselves in being **fast, flexible, and easy** to do business with. We provide an extensive connectivity offering and the ability to do **custom solutions** to meet the demands of any application. Combining these two, we offer the Connectivity In-Stock Program, ensuring you get what you need, when you need it.

Our Connectivity In-Stock Program ensures elevated levels of Turck stock on all of our standard connectivity products, resulting in **quicker shipping times** and fewer headaches for you. Turck is better suited than ever to work with you to develop the **perfect solution** for your application challenges, whether it comes from our In-Stock Program or a customized solution created specifically for your applications unique challenges.

Order from **Turck's Connectivity In-Stock Program**, and rest assured your order is on its way, because Turck works!

M8 Picofast



| SINGLE ENDED CORDSETS | | | | |
|----------------------------------|---------------|---------------|---------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS COUPLING NUT | | | | |
| 3 Pin | Male | Straight | PVC | PSG 3M-2 |
| | | | | PSG 3M-5 |
| | | | | PSG 3M-10 |
| | Female | Straight | PVC | PKG 3M-2 |
| | | | | PKG 3M-5 |
| | | | | PKG 3M-10 |
| | | | TPU | PKG 3M-2/S90 |
| | | | | PKG 3M-5/S90 |
| | | | | PKG 3M-10/S90 |
| | | Right Angle | PVC | PKW 3M-2 |
| | | | | PKW 3M-5 |
| | | | | PKW 3M-10 |
| TPU | PKW 3M-2/S90 | | | |
| | PKW 3M-5/S90 | | | |
| | PKW 3M-10/S90 | | | |
| 4 Pin | Male | Straight | PVC | PSG 4M-2 |
| | | | | PSG 4M-5 |
| | | | | PSG 4M-10 |
| | Female | Straight | PVC | PKG 4M-2 |
| | | | | PKG 4M-5 |
| | | | | PKG 4M-10 |
| | | | TPU | PKG 4M-2/S90 |
| | | | | PKG 4M-5/S90 |
| | | | | PKG 4M-10/S90 |
| | | Right Angle | PVC | PKW 4M-2 |
| | | | | PKW 4M-5 |
| | | | | PKW 4M-10 |
| | TPU | PKW 4M-2/S90 | | |
| | | PKW 4M-5/S90 | | |
| | | PKW 4M-10/S90 | | |
| STAINLESS STEEL COUPLING NUT | | | | |
| 3 Pin | Male | Straight | PVC | PSGV 3M-2 |
| | | | | PSGV 3M-5 |
| | | | | PSGV 3M-10 |
| | Female | Straight | PVC | PKG 3M-2 |
| | | | | PKG 3M-5 |
| | | | | PKG 3M-10 |
| | | TPU | PKG 3M-2/S90 | |
| | | | PKG 3M-5/S90 | |
| | | | PKG 3M-10/S90 | |

M8 Picofast

IN-STOCK PROGRAM

M8 Picofast



| EXTENSION CORDSETS | | | | |
|----------------------------------|-------------|-----------|------------|--|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS COUPLING NUT | | | | |
| 3 Pin | Male/Female | Straight | PVC | PKG 3M-2-PSG 3M PKG 3M-5-PSG 3M |
| | | | TPU | PKG 3M-2-PSG 3M/S90 PKG 3M-5-PSG 3M/S90 |
| 4 Pin | Male/Female | Straight | PVC | PKG 4M-2-PSG 4M PKG 4M-5-PSG 4M |
| | | | TPU | PKG 4M-2-PSG 4M/S90 PKG 4M-5-PSG 4M/S90 |
| STAINLESS STEEL COUPLING NUT | | | | |
| 3 Pin | Male/Female | Straight | PVC | PKG 3M-2-PSGV 3M PKG 3M-5-PSGV 3M |
| | | | TPU | PKG 3M-2-PSGV 3M/S90 PKG 3M-5-PSGV 3M/S90 |



| RECEPTACLES | | | |
|--|--------|----------------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS RECEPTACLE HOUSING | | | |
| 3 Pin | Male | Rear | MFS 3F-0.2 |
| | | Front | MFSS 3-0.2 |
| | Female | Front | MFKS 3-0.2 |
| | 4 Pin | Male | Rear |
| Front | | | MFSS 4-0.2 |
| | Female | Front | MFKS 4-0.2 |
| STAINLESS STEEL RECEPTACLE HOUSING | | | |
| 3 Pin | Male | Rear | MFSV 3F-0.2 |
| | | Front | MFSSV 3-0.2 |
| | Female | Front | MFKSV 3-0.2 |



| FIELD WIREABLES | | | |
|-----------------|--------|-----------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | PRODUCT DESCRIPTION |
| 3 Pin | Male | Straight | BS 5133-0 |
| | Female | Straight | B 5133-0 |
| 4 Pin | Male | Straight | BS 5143-0 |
| | Female | Straight | B 5143-0 |

M8 Picofast

IN-STOCK PROGRAM



| SINGLE ENDED CORDSETS | | | | |
|----------------------------------|--------------------------|------------------------|----------------------|----------------------|
| PIN COUNT | GENDER | PLUG BODY/ COLOR | CABLE TYPE/ COLOR | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS COUPLING NUT | | | | |
| 3 Pin | Male | Straight/ Yellow | PVC/Gray | RS 4T-2 |
| | | | | RS 4T-5 |
| | | | | RS 4T-10 |
| | Female | Straight/ Yellow | PVC/Gray | RK 4T-2 |
| | | | | RK 4T-5 |
| | | | | RK 4T-10 |
| | | | TPU/Gray | RK 4T-2/S90 |
| | | | | RK 4T-5/S90 |
| | | | | RK 4T-10/S90 |
| | | Right Angle/ Yellow | PVC/Gray | WK 4T-2 |
| | | | | WK 4T-5 |
| | | | | WK 4T-10 |
| | TPU/Gray | WK 4T-2/S90 | | |
| | | WK 4T-5/S90 | | |
| | | WK 4T-10/S90 | | |
| | Right Angle LED/Clear | PVC/Gray | WK 4T-2-P7X2 | |
| | | | WK 4T-5-P7X2 | |
| | | | WK 4T-10-P7X2 | |
| 4 Pin | Male | Straight/ Yellow | PVC/Gray | RS 4.4T-2 |
| | | | | RS 4.4T-5 |
| | | | | RS 4.4T-10 |
| | | Straight/ Black | PVC/Black | RS 4.4T-2/S760/S771 |
| | | | | RS 4.4T-5/S760/S771 |
| | | | | RS 4.4T-10/S760/S771 |
| | Female | Straight/ Yellow | PVC/Gray | RK 4.4T-2 |
| | | | | RK 4.4T-5 |
| | | | | RK 4.4T-10 |
| | | | TPU/Gray | RK 4.4T-2/S90 |
| | | | | RK 4.4T-5/S90 |
| | | | | RK 4.4T-10/S90 |
| | | Straight/ Black | PVC/Black | RK 4.4T-2/S760/S771 |
| | | | | RK 4.4T-5/S760/S771 |
| | | | | RK 4.4T-10/S760/S771 |
| | | Right Angle/ Yellow | PVC/Gray | WK 4.4T-2 |
| | | | | WK 4.4T-5 |
| | | | | WK 4.4T-10 |
| | TPU/Gray | | WK 4.4T-2/S90 | |
| | | | WK 4.4T-5/S90 | |
| | | | WK 4.4T-10/S90 | |
| Right Angle/ Black | PVC/ Black | WK 4.4T-2/S760/S771 | | |
| | | WK 4.4T-5/S760/S771 | | |
| | | WK 4.4T-10/S760/S771 | | |

M12 Eurofast



M12 Eurofast

IN-STOCK PROGRAM

| SINGLE ENDED CORDSETS (CONTINUED) | | | | |
|-----------------------------------|-----------|------------------------|----------------------|----------------------|
| PIN COUNT | GENDER | PLUG BODY/ COLOR | CABLE TYPE/ COLOR | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS COUPLING NUT | | | | |
| 5 Pin | Male | Straight/ Yellow | PVC/Gray | RS 4.5T-2 |
| | | | | RS 4.5T-5 |
| | | | | RS 4.5T-10 |
| | | Straight/ Black | PVC/ Black | RS 4.5T-2/S760/S771 |
| | | | | RS 4.5T-5/S760/S771 |
| | | | | RS 4.5T-10/S760/S771 |
| | Female | Straight/ Yellow | PVC/Gray | RK 4.5T-2 |
| | | | | RK 4.5T-5 |
| | | | | RK 4.5T-10 |
| | | Straight/Black | PVC/Black | RK 4.5T-2/S760/S771 |
| | | | | RK 4.5T-5/S760/S771 |
| | | | | RK 4.5T-10/S760/S771 |
| | | Right Angle/ Yellow | PVC/Gray | WK 4.5T-2 |
| | | | | WK 4.5T-5 |
| | | | | WK 4.5T-10 |
| Right Angle/ Black | PVC/Black | WK 4.5T-2/S760/S771 | | |
| | | WK 4.5T-5/S760/S771 | | |
| | | WK 4.5T-10/S760/S771 | | |
| 8 Pin | Male | Straight/ Yellow | PVC/Gray | RSC 8T-2 |
| | | | | RSC 8T-5 |
| | | | | RSC 8T-10 |
| | Female | Straight/ Yellow | PVC/Gray | RKC 8T-2 |
| | | | | RKC 8T-5 |
| | | | | RKC 8T-10 |



| SINGLE ENDED CORDSETS (CONTINUED) | | | | | |
|-----------------------------------|------------------------------|------------------------|----------------------|---------------------|-------------|
| PIN COUNT | GENDER | PLUG BODY/ COLOR | CABLE TYPE/ COLOR | PRODUCT DESCRIPTION | |
| STAINLESS STEEL COUPLING NUT | | | | | |
| 3 Pin | Male | Straight/ Yellow | PVC/Gray | RSV 4T-2 | |
| | | | | RSV 4T-5 | |
| | | | | RSV 4T-10 | |
| | Female | Straight/ Yellow | PVC/Gray | RKV 4T-2 | |
| | | | | RKV 4T-5 | |
| | | | | RKV 4T-10 | |
| | | | TPU/Gray | RKV 4T-2/S90 | |
| | | | | RKV 4T-5/S90 | |
| | | | | RKV 4T-10/S90 | |
| | | Right Angle/ Yellow | PVC/Gray | WKV 4T-2 | |
| | | | | WKV 4T-5 | |
| | | | | WKV 4T-10 | |
| | TPU/Gray | | WKV 4T-2/S90 | | |
| | | | WKV 4T-5/S90 | | |
| | | | WKV 4T-10/S90 | | |
| | Right Angle LED/ Clear | PVC/Gray | WKV 4T-2-P7X2 | | |
| | | | WKV 4T-5-P7X2 | | |
| | | | WKV 4T-10-P7X2 | | |
| 4 Pin | Male | Straight/ Yellow | PVC/Gray | RSV 4.4T-2 | |
| | | | | RSV 4.4T-5 | |
| | | | | RSV 4.4T-10 | |
| | Female | Straight/ Yellow | PVC/Gray | RKV 4.4T-2 | |
| | | | | RKV 4.4T-5 | |
| | | | | RKV 4.4T-10 | |
| | | | TPU/Gray | RKV 4.4T-2/S90 | |
| | | | | RKV 4.4T-5/S90 | |
| | | | | RKV 4.4T-10/S90 | |
| | | Right Angle/ Yellow | PVC/Gray | WKV 4.4T-2 | |
| | | | | WKV 4.4T-5 | |
| | | | | WKV 4.4T-10 | |
| | TPU/Gray | | WKV 4.4T-2/S90 | | |
| | | | WKV 4.4T-5/S90 | | |
| | | | WKV 4.4T-10/S90 | | |
| | 5 Pin | Male | Straight/ Yellow | PVC/Gray | RSV 4.5T-2 |
| | | | | | RSV 4.5T-5 |
| | | | | | RSV 4.5T-10 |
| Female | | Straight/ Yellow | PVC/Gray | RKV 4.5T-2 | |
| | | | | RKV 4.5T-5 | |
| | | | | RKV 4.5T-10 | |
| | | Right Angle/ Yellow | PVC/Gray | WKV 4.5T-2 | |
| | | | | WKV 4.5T-5 | |
| | | | | WKV 4.5T-10 | |

M12 Eurofast



M12 Eurofast

IN-STOCK PROGRAM

| EXTENSION CORDSETS | | | | |
|----------------------------------|-------------|---------------------|----------------------|-----------------------------|
| PIN COUNT | GENDER | PLUG BODY/ COLOR | CABLE TYPE/ COLOR | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS COUPLING NUT | | | | |
| 3 Pin | Male/Female | Straight/Yellow | PVC/Gray | RK 4T-1-RS 4T |
| | | | | RK 4T-2-RS 4T |
| | | | | RK 4T-5-RS 4T |
| | | | TPU/Gray | RK 4T-1-RS 4T/S90 |
| | | | | RK 4T-2-RS 4T/S90 |
| | | | | RK 4T-5-RS 4T/S90 |
| 4 Pin | Male/Female | Straight/Yellow | PVC/Gray | RK 4.4T-1-RS 4.4T |
| | | | | RK 4.4T-2-RS 4.4T |
| | | | | RK 4.4T-5-RS 4.4T |
| | | | TPU/Gray | RK 4.4T-1-RS 4.4T/S90 |
| | | | | RK 4.4T-2-RS 4.4T/S90 |
| | | | | RK 4.4T-5-RS 4.4T/S90 |
| | | Straight/Black | PVC/ Black | RK 4.4T-1-RS 4.4T/S760/S771 |
| | | | | RK 4.4T-2-RS 4.4T/S760/S771 |
| | | | | RK 4.4T-5-RS 4.4T/S760/S771 |
| 5 Pin | Male/Female | Straight/Yellow | PVC/Gray | RK 4.5T-1-RS 4.5T |
| | | | | RK 4.5T-2-RS 4.5T |
| | | | | RK 4.5T-5-RS 4.5T |
| | | Straight/Black | PVC/Black | RK 4.5T-1-RS 4.5T/S760/S771 |
| | | | | RK 4.5T-2-RS 4.5T/S760/S771 |
| | | | | RK 4.5T-5-RS 4.5T/S760/S771 |
| 8 Pin | Male/Female | Straight/Yellow | PVC/Gray | RKC 8T-1-RSC 8T |
| | | | | RKC 8T-2-RSC 8T |
| | | | | RKC 8T-5-RSC 8T |
| STAINLESS STEEL COUPLING NUT | | | | |
| 4 Pin | Male/Female | Straight/Yellow | PVC/Gray | RKV 4.4T-2-RSV 4.4T |
| | | | | RKV 4.4T-5-RSV 4.4T |
| 5 Pin | Male/Female | Straight/Yellow | PVC/Gray | RKV 4.5T-2-RSV 4.5T |
| | | | | RKV 4.5T-5-RSV 4.5T |

M12 Eurofast



| RECEPTACLES | | | | |
|--|---------------------|----------------|---------------------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | PRODUCT DESCRIPTION | |
| NICKEL PLATED BRASS RECEPTACLE HOUSING | | | | |
| 4 Pin | Male | Front | FS 4.4-0.5 | |
| | | | FS 4.4-0.5/18.25 | |
| | FS 4.4-0.5/14.5/NPT | | | |
| | Female | Rear | Front | FSFD 4.4-0.5 |
| | | | | FK 4.4-0.5 |
| | | Feed-Thru | Rear | FK 4.4-0.5/18.25 |
| | | | | FK 4.4-0.5/14.5/NPT |
| FKFD 4.4-0.5 | | | | |
| FK FS 4.4/M12 | | | | |
| 5 Pin | Male | Front | FS 4.5-0.5 | |
| | | | FS 4.5-0.5/18.25 | |
| | FS 4.5-0.5/14.5/NPT | | | |
| | Female | Rear | Front | FSFD 4.5-0.5 |
| | | | | FK 4.5-0.5 |
| | | Feed-Thru | Rear | FK 4.5-0.5/18.25 |
| | | | | FK 4.5-0.5/14.5/NPT |
| FKFD 4.5-0.5 | | | | |
| FK FS 4.5/M12 | | | | |
| 8 Pin | Male | Front | FS 8-0.5 | |
| | | | FS 8-0.5/18.25 | |
| | FS 8-0.5/14.5/NPT | | | |
| | Female | Rear | Front | FSFD 8-0.5 |
| | | | | FK 8-0.5 |
| | | Feed-Thru | Rear | FK 8-0.5/18.25 |
| | | | | FK 8-0.5/14.5/NPT |
| FKFD 8-0.5 | | | | |
| FK FS 8/M12 | | | | |

M12 Eurofast

IN-STOCK PROGRAM

M12 Eurofast



M12 Eurofast

| RECEPTACLES (CONTINUED) | | | | |
|------------------------------------|--------|----------------------|----------------------|--|
| PIN COUNT | GENDER | MOUNTING STYLE | PRODUCT DESCRIPTION | |
| STAINLESS STEEL RECEPTACLE HOUSING | | | | |
| 4 Pin | Male | Front | FSV 4.4-0.5 | |
| | | | FSV 4.4-0.5/18.25 | |
| | | | FSV 4.4-0.5/14.5/NPT | |
| | Rear | | FSFDV 4.4-0.5 | |
| | Female | Front | FKV 4.4-0.5 | |
| | | | FKV 4.4-0.5/18.25 | |
| | | FKV 4.4-0.5/14.5/NPT | | |
| Rear | | FKFDV 4.4-0.5 | | |
| Male to Female | | Feed-Thru | FKV FSV 4.4/M12 | |
| 5 Pin | Male | Front | FSV 4.5-0.5 | |
| | | | FSV 4.5-0.5/18.25 | |
| | | | FSV 4.5-0.5/14.5/NPT | |
| | Rear | | FSFDV 4.5-0.5 | |
| | Female | Front | FKV 4.5-0.5 | |
| | | | FKV 4.5-0.5/18.25 | |
| | | FKV 4.5-0.5/14.5/NPT | | |
| Rear | | FKFDV 4.5-0.5 | | |
| Male to Female | | Feed-Thru | FKV FSV 4.5/M12 | |



| PCB PIN RECEPTACLES | | | | |
|---------------------|--------|----------------|-----------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | PIN STYLE | PRODUCT DESCRIPTION |
| 4 Pin | Male | Rear | Short Pin | FSFDK 4.4 |
| | | | Long Pin | FSFD 4.4 |
| Female | | Rear | Long Pin | FKFD 4.4 |
| 5 Pin | Male | Rear | Short Pin | FSFDK 4.5 |
| | | | Long Pin | FSFD 4.5 |
| Female | | Rear | Short Pin | FKFDK 4.5 |
| | | | Long Pin | FKFD 4.5 |
| 8 Pin | Male | Rear | Short Pin | FSFDK 8-PCB |
| | | | Long Pin | FSFD 8 |
| Female | | Rear | Short Pin | FKFDK 8-PCB |
| | | | Long Pin | FKFD 8 |

IN-STOCK PROGRAM

M12 Eurofast



| FIELD WIREABLES | | | |
|-----------------|--------|-------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | PRODUCT DESCRIPTION |
| 4 Pin | Male | Straight | BS 8141-0 |
| | | | BS 8141-0/PG 9 |
| | Female | Right Angle | BS 8241-0 |
| | | Straight | B 8141-0 |
| | | | B 8141-0/PG 9 |
| | | Right Angle | B 8241-0 |
| 5 Pin | Male | Straight | BS 8151-0/PG9 |
| | | Right Angle | BS 8251-0/PG9 |
| | Female | Straight | B 8151-0/PG9 |
| | | Right Angle | B 8251-0/PG9 |

M12 Eurofast

IN-STOCK PROGRAM

7/8" Minifast



7/8" Minifast

IN-STOCK PROGRAM

| SINGLE ENDED CORDSETS | | | | |
|----------------------------------|--------|-----------|-------------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| NICKEL PLATED BRASS COUPLING NUT | | | | |
| 3 Pin | Male | Straight | PVC/18 AWG | RSM 30-2M |
| | | | | RSM 30-5M |
| | | | | RSM 30-10M |
| | | | PVC/16 AWG | RSM 36-2M |
| | | | | RSM 36-5M |
| | | | | RSM 36-10M |
| | Female | Straight | PVC/18 AWG | RKM 30-2M |
| | | | | RKM 30-5M |
| | | | | RKM 30-10M |
| | | | PVC/16 AWG | RKM 36-2M |
| | | | | RKM 36-5M |
| | | | | RKM 36-10M |
| 4 Pin | Male | Straight | PVC/18 AWG | RSM 40-2M |
| | | | | RSM 40-5M |
| | | | | RSM 40-10M |
| | | | PVC/16 AWG | RSM 46-2M |
| | | | | RSM 46-5M |
| | | | | RSM 46-10M |
| | Female | Straight | PVC/18 AWG | RKM 40-2M |
| | | | | RKM 40-5M |
| | | | | RKM 40-10M |
| | | | PVC/16 AWG | RKM 46-2M |
| | | | | RKM 46-5M |
| | | | | RKM 46-10M |
| 5 Pin | Male | Straight | PVC/18 AWG | RSM 50-2M |
| | | | | RSM 50-5M |
| | | | | RSM 50-10M |
| | | | PVC/16 AWG | RSM 56-2M |
| | | | | RSM 56-5M |
| | | | | RSM 56-10M |
| | Female | Straight | PVC/18 AWG | RKM 50-2M |
| | | | | RKM 50-5M |
| | | | | RKM 50-10M |
| | | | PVC/16 AWG | RKM 56-2M |
| | | | | RKM 56-5M |
| | | | | RKM 56-10M |

7/8" Minifast



| SINGLE ENDED CORDSETS (CONTINUED) | | | | |
|-----------------------------------|--------|-----------|-------------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| STAINLESS STEEL COUPLING NUT | | | | |
| 3 Pin | Male | Straight | PVC/18 AWG | RSV 30-5M |
| | Female | | PVC/18 AWG | RKV 30-5M |
| 4 Pin | Male | Straight | PVC/18 AWG | RSV 40-5M |
| | Female | | PVC/18 AWG | RKV 40-5M |
| 5 Pin | Male | Straight | PVC/18 AWG | RSV 50-5M |
| | Female | | PVC/18 AWG | RKV 50-5M |

7/8" Minifast

IN-STOCK PROGRAM

7/8" Minifast



| EXTENSION CORDSETS | | | | |
|--------------------|-------------|-----------|-------------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| 3 Pin | Male/Female | Straight | PVC/18 AWG | RSM RKM 30-2M |
| | | | | RSM RKM 30-5M |
| | | | PVC/16 AWG | RSM RKM 36-2M |
| | | | | RSM RKM 36-5M |
| 4 Pin | Male/Female | Straight | PVC/18 AWG | RSM RKM 40-2M |
| | | | | RSM RKM 40-5M |
| | | | PVC/16 AWG | RSM RKM 46-2M |
| | | | | RSM RKM 46-5M |
| 5 Pin | Male/Female | Straight | PVC/18 AWG | RSM RKM 50-2M |
| | | | | RSM RKM 50-5M |
| | | | PVC/16 AWG | RSM RKM 56-2M |
| | | | | RSM RKM 56-5M |



| RECEPTACLES | | | | |
|----------------|-----------|----------------|---------------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | AWG | PRODUCT DESCRIPTION |
| 3 Pin | Male | Front | 18 AWG | RSF 30-1M |
| | | | | RSF 30-1M/NPT |
| | | | 16 AWG | RSF 36-1M |
| | | | | RSF 36-1M/NPT |
| | Female | Front | 18 AWG | RKF 30-1M |
| | | | | RKF 30-1M/NPT |
| | | | 16 AWG | RKF 36-1M |
| | | | | RKF 36-1M/NPT |
| Male to Female | Feed-Thru | 18 AWG | RSF RKF 30/22 | |

7/8" Minifast

IN-STOCK PROGRAM

| RECEPTACLES (CONTINUED) | | | | |
|-------------------------|---------------|----------------|---------------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | AWG | PRODUCT DESCRIPTION |
| 4 Pin | Male | Front | 18 AWG | RSF 40-1M |
| | | | | RSF 40-1M/NPT |
| | | | 16 AWG | RSF 46-1M |
| | RSF 46-1M/NPT | | | |
| | Female | Front | 18 AWG | RKF 40-1M |
| | | | | RKF 40-1M/NPT |
| 16 AWG | | | RKF 46-1M | |
| | RKF 46-1M/NPT | | | |
| Male to Female | Feed-Thru | 18 AWG | RSF RKF 40/22 | |
| 5 Pin | Male | Front | 18 AWG | RSF 50-1M |
| | | | | RSF 50-1M/NPT |
| | | | 16 AWG | RSF 56-1M |
| | RSF 56-1M/NPT | | | |
| | Female | Front | 18 AWG | RKF 50-1M |
| | | | | RKF 50-1M/NPT |
| 16 AWG | | | RKF 56-1M | |
| | RKF 56-1M/NPT | | | |
| Male to Female | Feed-Thru | 18 AWG | RSF RKF 50/22 | |



| FIELD WIREABLES | | | |
|-----------------|--------|-----------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | PRODUCT DESCRIPTION |
| 3 Pin | Male | Straight | BS 4131-0/9 |
| | | | BS 4131-0/13.5 |
| | Female | Straight | B 4131-0/9 |
| | | | B 4131-0/13.5 |
| 4 Pin | Male | Straight | BS 4141-0/9 |
| | | | BS 4141-0/13.5 |
| | Female | Straight | B 4141-0/9 |
| | | | B 4141-0/13.5 |
| 5 Pin | Male | Straight | BS 4151-0/9 |
| | | | BS 4151-0/13.5 |
| | Female | Straight | B 4151-0/9 |
| | | | B 4151-0/13.5 |

M12 Junction Boxes



M12 JUNCTION BOXES

IN-STOCK PROGRAM

| M12 JUNCTION BOXES | | | |
|--------------------------------|-----------------------------------|-----------------------------------|---------------------|
| # OF PORTS | SIGNALS PER PORT | HOMERUN CONNECTOR | PRODUCT DESCRIPTION |
| 4-Port | 1 Signal Per Port | Top Exit 12-Pin multifast | 4MB12Z-4-CS12 |
| | | Side Exit 12-Pin multifast | 4MB12Z-4-CS12H |
| | 1 Signal Per Port/ PNP LED | Top Exit 12-Pin multifast | 4MB12Z-4P2-CS12 |
| | | Side Exit 12-Pin multifast | 4MB12Z-4P2-CS12H |
| | 2 Signals Per Port | Top Exit 19-Pin multifast | 4MB12Z-5-CS19 |
| | | Side Exit 19-Pin multifast | 4MB12Z-5-CS19H |
| 2 Signals Per Port/ PNP LED | Top Exit 19-Pin multifast | 4MB12Z-5P3-CS19 | |
| | Side Exit 19-Pin multifast | 4MB12Z-5P3-CS19H | |
| 6-Port | 1 Signal Per Port | Top Exit 12-Pin multifast | 6MB12Z-4-CS12 |
| | | Side Exit 12-Pin multifast | 6MB12Z-4-CS12H |
| | 1 Signal Per Port/ PNP LED | Top Exit 12-Pin multifast | 6MB12Z-4P2-CS12 |
| | | Side Exit 12-Pin multifast | 6MB12Z-4P2-CS12H |
| | 2 Signals Per Port | Top Exit 19-Pin multifast | 6MB12Z-5-CS19 |
| | | Side Exit 19-Pin multifast | 6MB12Z-5-CS19H |
| 2 Signals Per Port/ PNP LED | Top Exit 19-Pin multifast | 6MB12Z-5P3-CS19 | |
| | Side Exit 19-Pin multifast | 6MB12Z-5P3-CS19H | |
| 8-Port | 1 Signal Per Port | Top Exit 12-Pin multifast | 8MB12Z-4-CS12 |
| | | Side Exit 12-Pin multifast | 8MB12Z-4-CS12H |
| | 1 Signal Per Port/ PNP LED | Top Exit 12-Pin multifast | 8MB12Z-4P2-CS12 |
| | | Side Exit 12-Pin multifast | 8MB12Z-4P2-CS12H |
| | 2 Signals Per Port | Top Exit 19-Pin multifast | 8MB12Z-5-CS19 |
| | | Side Exit 19-pin multifast | 8MB12Z-5-CS19H |
| 2 Signals Per Port/ PNP LED | Top Exit 19-Pin multifast | 8MB12Z-5P3-CS19 | |
| | Side Exit 19-Pin multifast | 8MB12Z-5P3-CS19H | |



| SINGLE ENDED CORDSETS | | | | |
|-----------------------|--------|-----------|------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE | PRODUCT DESCRIPTION |
| 12 Pin | Female | Straight | PVC | CKCM 12-7-5 |
| | | | | CKCM 12-7-10 |
| | | | | CKCM 12-9-5 |
| | | | | CKCM 12-9-10 |
| | | | | CKCM 12-11-5 |
| | | | | CKCM 12-11-10 |
| 19 Pin | Female | Straight | PVC | CKM 19-11-5 |
| | | | | CKM 19-11-10 |
| | | | | CKM 19-15-5 |
| | | | | CKM 19-15-10 |
| | | | | CKM 19-19-5 |
| | | | | CKM 19-19-10 |



| EXTENSION CORDSETS | | | | |
|--------------------|-------------|-----------|------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE | PRODUCT DESCRIPTION |
| 12 Pin | Male/Female | Straight | PVC | CSCM CKCM 12-11-5 |
| 19 Pin | Male/Female | Straight | PVC | CSM CKM 19-19-5 |



| RECEPTACLES | | | |
|-------------|--------|----------------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | PRODUCT DESCRIPTION |
| 12 pin | Female | Front | CKCF 12-11-1 |
| 19 pin | Female | Front | CKF 19-19-1 |

Splitters



| VB2 SPLITTERS | | |
|---------------------------------------|-------------------------|---------------------------|
| HOMERUN CONNECTOR/ PORT CONNECTORS | WIRING | PRODUCT DESCRIPTION |
| Integral M12/Integral M12 | Standard 4-Wire | VB2-FSM 4.4/2FKM 4 |
| | Parallel 4-Wire | VB2-FSM 4.4/2FKM 4.4/S651 |
| | Series 4-Wire | VB2-FSM 4.4/2FKM 4/S719 |
| | Parallel 5-Wire | VB2-FSM 4.5/2FKM 4.5/S651 |
| | Standard 4-Wire/PNP LED | VB2-PX3-FSM 4.4/2FKM 4 |



| YB2 SPLITTERS | | |
|---------------------------------------|-----------------|----------------------------|
| HOMERUN CONNECTOR/ PORT CONNECTORS | WIRING | PRODUCT DESCRIPTION |
| Integral M12/Integral M12 | Standard 5-Wire | YB2-FSM 4.5-2FKM 4.5 |
| | Standard 5-Wire | YB2-FSM 4.5-2FKM 4.5/S1063 |
| Integral M12/Integral M8 | Standard 4-Wire | YB2-FSM 4.4/2PKG 3M |



| VBRS SPLITTERS | | |
|---------------------------------------|-----------------|--------------------------|
| HOMERUN CONNECTOR/ PORT CONNECTORS | WIRING | PRODUCT DESCRIPTION |
| Integral M12/M12 Cables | Standard 4-Wire | VBRS 4.4-2RK 4T-0.3/0.3 |
| Integral M12/M8 Cables | Standard 4-Wire | VBRS 4.4-2PKG 3M-0.3/0.3 |
| Integral M12/Integral M8 | Standard 4-Wire | VBRS 4.4-2SKM 3 |

SPLITTERS

IN-STOCK PROGRAM



| ETHERNET PATCH CORDS | | |
|----------------------------------|------------------|---------------------------|
| CABLE TYPE | TERMINATION TYPE | PRODUCT DESCRIPTION |
| 440 - Stranded Unshielded/2 Pair | RJ45/RJ45 | RJ45 RJ45 440-1M |
| | | RJ45 RJ45 440-2M |
| | M12/M12 | RSCD RSCD 440-1M |
| | | RSCD RSCD 440-2M |
| | | RSCD RSCD 440-5M |
| | | RSCD RSCD 440-10M |
| | | RSCD RSCD 440-20M |
| | M12/RJ45 | RSCD RJ45 440-2M |
| | | RSCD RJ45 440-5M |
| | | RSCD RJ45 440-10M |
| 441 - Stranded Shielded/2 Pair | RJ45/RJ45 | RJ45S RJ45S 441-1M |
| | | RJ45S RJ45S 441-2M |
| | | RJ45S RJ45S 441-5M |
| | | RJ45S RJ45S 441-10M |
| | M12/M12 | RSSD RSSD 441-1M |
| | | RSSD RSSD 441-2M |
| | | RSSD RSSD 441-5M |
| | | RSSD RSSD 441-10M |
| | | RSSD RSSD 441-20M |
| | M12/RJ45 | RSSD RJ45S 441-1M |
| | | RSSD RJ45S 441-2M |
| | | RSSD RJ45S 441-5M |
| | | RSSD RJ45S 441-10M |
| 4413 - Stranded Shielded/2 Pair | M8/M8 | PSGS 4M PSGS 4M 4413-0.2M |
| | | PSGS 4M PSGS 4M 4413-0.3M |
| | | PSGS 4M PSGS 4M 4413-0.5M |
| | | PSGS 4M PSGS 4M 4413-0.6M |
| | | PSGS 4M PSGS 4M 4413-1M |
| | | PSGS 4M PSGS 4M 4413-2M |
| | | PSGS 4M PSGS 4M 4413-5M |
| | M12/M8 | RSSD PSGS 4M 4413-0.5M |
| | M8/RJ45 | PSGS 4M RJ45S 4413-0.5M |
| | | PSGS 4M RJ45S 4413-1M |
| | | PSGS 4M RJ45S 4413-2M |

Ethernet

Ethernet

| ETHERNET PATCH CORDS (CONTINUED) | | |
|----------------------------------|--------------------------------|---------------------|
| CABLE TYPE | TERMINATION TYPE | PRODUCT DESCRIPTION |
| 840- Stranded Unshielded/4 Pair | RJ45/RJ45 | RJ45 RJ45 840-1M |
| | | RJ45 RJ45 840-2M |
| | | RJ45 RJ45 840-5M |
| | M12/RJ45 | RSC RJ45 840-1M |
| | | RSC RJ45 840-2M |
| | | RSC RJ45 840-5M |
| | | RSC RJ45 840-10M |
| | 841 - Stranded Shielded/4 Pair | RJ45/RJ45 |
| RJ45S RJ45S 841-2M | | |
| RJ45S RJ45S 841-5M | | |
| RJ45S RJ45S 841-10M | | |
| M12/M12 | | RSS RSS 841-2M |
| | | RSS RSS 841-5M |
| | | RSS RSS 841-10M |
| M12/RJ45 | | RSS RJ45S 841-1M |
| | | RSS RJ45S 841-2M |
| | | RSS RJ45S 841-5M |
| | | RSS RJ45S 841-10M |



| PANEL & FIELD WIREABLE ACCESSORIES | | | |
|------------------------------------|-------------|----------------------------|----------------------------|
| PIN COUNT | CONNECTOR | TYPE | PRODUCT DESCRIPTION |
| 4 Pin | M12 to RJ45 | Feed-Thru | FKSDD RJ45SF 44 |
| | M12 | PCB Mount Receptacle | FKFDD 44-PCB |
| | M12 | Field Wireable | CMBSD 8141-0/PG9 |
| | RJ45 | Field Wireable | CONNECTOR, RJ45S IDC |
| 5 Pin | M12 | PCB Mount Receptacle | FKFD 84-PCB |
| | M12 | Short PCB Mount Receptacle | FKFD 84-PCB/S |
| | RJ45 | Field Wireable | CONNECTOR, FW,RJ45S 84 IDC |

IN-STOCK PROGRAM



| SINGLE ENDED CORDSETS | | | | | |
|-----------------------|--------|-----------|------------|------------|---------------------|
| CONNECTOR TYPE | GENDER | PLUG BODY | CABLE TYPE | CABLE TYPE | PRODUCT DESCRIPTION |
| M12 | Male | Straight | PVC | Thin | RSC 572-0.5M |
| | | | | | RSC 572-1M |
| | | | | | RSC 572-2M |



| EXTENSION CORDSETS | | | | | |
|----------------------|-------------|-----------|------------|------------|---------------------|
| CONNECTOR TYPE | GENDER | PLUG BODY | CABLE TYPE | CABLE TYPE | PRODUCT DESCRIPTION |
| M12 | Male/Female | Straight | PVC | Thin | RSC RKC 572-1M |
| | | | | | RSC RKC 572-2M |
| | | | | | RSC RKC 572-5M |
| | | | | | RSC RKC 572-10M |
| 7/8" <i>minifast</i> | Male/Female | Straight | PVC | Thin | RSM RKM 572-1M |
| | | | | | RSM RKM 572-2M |
| | | | | Thick | RSM RKM 579-1M |
| | | | | | RSM RKM 579-2M |
| | | | | | RSM RKM 579-5M |
| | | | | | RSM RKM 579-10M |



DeviceNet



| ACCESSORIES | | |
|----------------------|--------------------|---------------------|
| CONNECTOR TYPE | CONNECTORS | PRODUCT DESCRIPTION |
| Bus Drop Tee | 7/8" with M12 Drop | RSM FKM RKM 57 |
| | 7/8" | RSM 2RKM 57 |
| | M12 | RSC 2RKC 57 |
| Gender Changer | M12 | RSC WKC 57 |
| Terminating Resistor | M12 | RSE 57-TR2 |
| | | RKE 57-TR2 |
| | 7/8" | RSM 57-TR2 |
| | | RKM 57-TR2 |

DeviceNet

IN-STOCK PROGRAM

Valve Plugs



| TYPE A - 18mm | | | | |
|---|----------------|----------------|----------------|---------------------|
| PINOUT | WIRING | VOLTAGE | CABLE TYPE | PRODUCT DESCRIPTION |
| 2 Conductors + 1 Ground, Ground Contacts Parallel Wired | Straight | 0-220V | PVC | VAS 22-A653-2M |
| | | | | VAS 22-A653-5M |
| | | | TPU | VAS 22-A669-2M |
| | | | | VAS 22-A669-5M |
| | LED | 110-220V | PVC | VAS 22-C653-2M |
| | | | | VAS 22-C653-5M |
| | | | TPU | VAS 22-C669-2M |
| | | | | VAS 22-C669-5M |
| | LED/MOV | 24-48V | PVC | VAS 22-D653-2M |
| | | | | VAS 22-D653-5M |
| | | | TPU | VAS 22-D669-2M |
| | | VAS 22-D669-5M | | |
| | | 110-220V | PVC | VAS 22-E653-2M |
| | | | | VAS 22-E653-5M |
| TPU | VAS 22-E669-2M | | | |
| | VAS 22-E669-5M | | | |
| LED/DIODE | 24-48VDC | PVC | VAS 22-F653-2M | |
| | | | VAS 22-F653-5M | |
| | | TPU | VAS 22-F669-2M | |
| | | | VAS 22-F669-5M | |
| 3 Conductors + Ground | Straight | 0-220V | PVC | VAS 3-A580-2M |
| | | | | VAS 3-A580-5M |

VALVE PLUGS

IN-STOCK PROGRAM

Valve Plugs



VALVE PLUGS

| TYPE I - 11mm | | | | |
|----------------------------|-----------|----------|------------|---------------------|
| PINOUT | WIRING | VOLTAGE | CABLE TYPE | PRODUCT DESCRIPTION |
| 2 Conductors + 1 Ground | Straight | 0-220V | PVC | VIS 2-A653-5M |
| | | | TPU | VIS 2-A669-5M |
| | LED | 24-48V | PVC | VIS 2-B653-5M |
| | | | TPU | VIS 2-B669-5M |
| | LED/MOV | 24-48V | PVC | VIS 2-D653-5M |
| | | | TPU | VIS 2-D669-5M |
| | | 110-220V | PVC | VIS 2-E653-5M |
| | | | TPU | VIS 2-E669-5M |
| | LED/DIODE | 24-48VDC | PVC | VIS 2-F653-5M |
| | | | TPU | VIS 2-F669-5M |



| TYPE B - 10mm | | | | |
|----------------------------|-----------|----------|------------|---------------------|
| PINOUT | WIRING | VOLTAGE | CABLE TYPE | PRODUCT DESCRIPTION |
| 2 Conductors + 1 Ground | Straight | 0-220V | PVC | VBS 2-A653-5M |
| | | | TPU | VBS 2-A669-5M |
| | LED | 24-48V | PVC | VBS 2-B653-5M |
| | | | TPU | VBS 2-B669-5M |
| | LED/MOV | 24-48V | PVC | VBS 2-D653-5M |
| | | | TPU | VBS 2-D669-5M |
| | LED/DIODE | 24-48VDC | PVC | VBS 2-F653-5M |
| | | | TPU | VBS 2-F669-5M |

IN-STOCK PROGRAM

Valve Plugs



| TYPE C - 9.4mm | | | | |
|-------------------------|------------|---------|------------|---------------------|
| PINOUT | WIRING | VOLTAGE | CABLE TYPE | PRODUCT DESCRIPTION |
| 2 Conductors + 1 Ground | Straight | 0-220V | PVC | TC9S 2-A653-5M |
| | | | TPU | TC9S 2-A669-5M |
| | LED | 24V | PVC | TC9S 2-L653-5M |
| | | | TPU | TC9S 2-L669-5M |
| | LED/DIODES | 24V | PVC | TC9S 2-P653-5M |
| | | | TPU | TC9S 2-P669-5M |



| TYPE C - 8mm | | | | |
|-------------------------|------------|---------|------------|---------------------|
| PINOUT | WIRING | VOLTAGE | CABLE TYPE | PRODUCT DESCRIPTION |
| 2 Conductors + 1 Ground | Straight | 0-220V | PVC | TC8S 2-A653-5M |
| | | | TPU | TC8S 2-A669-5M |
| | LED | 24V | PVC | TC8S 2-L653-5M |
| | | | TPU | TC8S 2-L669-5M |
| | | 110V | PVC | TC8S 2-N653-5M |
| | | | TPU | TC8S 2-N669-5M |
| | LED/DIODES | 24V | PVC | TC8S 2-P653-5M |
| | | | TPU | TC8S 2-P669-5M |



| EXTENSION CORDSETS - VALVE TO M12 | | | | |
|---|-----------|----------|------------|------------------------|
| PINOUT | WIRING | VOLTAGE | CABLE TYPE | PRODUCT DESCRIPTION |
| Type A 2 Conductors + 1 Ground, Ground Contacts Parallel Wired | Straight | 0-220V | PVC | VAS 22-A653-2M-RS 5.3T |
| | LED/DIODE | 24-48VDC | PVC | VAS 22-F653-2M-RS 5.3T |
| Type I 2 Conductors + 1 Ground | Straight | 0-220V | PVC | VIS 2-A653-2M-RS 5.3T |
| | LED/DIODE | 24-48VDC | PVC | VIS 2-F653-2M-RS 5.3T |

VALVE PLUGS

IN-STOCK PROGRAM

A-Size Powerfast



| SINGLE ENDED CORDSETS | | | | |
|-----------------------|--------|-----------|-------------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| 3 Pin | Male | Straight | TPE TC-ER/14 AWG | RSM 34-2M/S4000 |
| | | | | RSM 34-5M/S4000 |
| | | | | RSM 34-10M/S4000 |
| | Female | Straight | TPE TC-ER/14 AWG | RKM 34-2M/S4000 |
| | | | | RKM 34-5M/S4000 |
| | | | | RKM 34-10M/S4000 |
| 4 Pin | Male | Straight | TPE TC-ER/14 AWG | RSM 44-2M/S4000 |
| | | | | RSM 44-5M/S4000 |
| | | | | RSM 44-10M/S4000 |
| | Female | Straight | TPE TC-ER/14 AWG | RKM 44-2M/S4000 |
| | | | | RKM 44-5M/S4000 |
| | | | | RKM 44-10M/S4000 |



| EXTENSION CORDSETS | | | | |
|--------------------|-------------|-----------|-------------------|----------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| 3 Pin | Male/Female | Straight | TPE TC-ER/14 AWG | RSM RKM 34-2M/S4000 |
| | | | | RSM RKM 34-5M/S4000 |
| | | | | RSM RKM 34-10M/S4000 |
| 4 Pin | Male/Female | Straight | TPE TC-ER/14 AWG | RSM RKM 44-2M/S4000 |
| | | | | RSM RKM 44-5M/S4000 |
| | | | | RSM RKM 44-10M/S4000 |

A-SIZE Powerfast

IN-STOCK PROGRAM

A-Size Powerfast



| RECEPTACLES | | | |
|-------------|--------|----------------|---------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | PRODUCT DESCRIPTION |
| 3 Pin | Male | 1/2" NPT | RSF 34-0.5M/NPT |
| | | | RSF 34-2M/NPT |
| | Female | 1/2" NPT | RKF 34-0.5M/NPT |
| | | | RKF 34-2M/NPT |
| 4 Pin | Male | 1/2" NPT | RSF 44-0.5M/NPT |
| | | | RSF 44-2M/NPT |
| | Female | 1/2" NPT | RKF 44-0.5M/NPT |
| | | | RKF 44-2M/NPT |

A-SIZE Powerfast

IN-STOCK PROGRAM

D-Size Powerfast



| SINGLE ENDED CORDSETS | | | | |
|-----------------------|--------|-----------|-------------------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| 3 Pin | Male | Straight | PVC TC-ER/10 AWG | GSDA 30-2M/S4000 |
| | | | | GSDA 30-5M/S4000 |
| | | | | GSDA 30-10M/S4000 |
| | Female | Straight | PVC TC-ER/10 AWG | GKDA 30-2M/S4000 |
| | | | | GKDA 30-5M/S4000 |
| | | | | GKDA 30-10M/S4000 |
| 4 Pin | Male | Straight | PVC TC-ER/10 AWG | GSDA 40-2M/S4000 |
| | | | | GSDA 40-5M/S4000 |
| | | | | GSDA 40-10M/S4000 |
| | Female | Straight | PVC TC-ER/10 AWG | GKDA 40-2M/S4000 |
| | | | | GKDA 40-5M/S4000 |
| | | | | GKDA 40-10M/S4000 |



| EXTENSION CORDSETS | | | | |
|--------------------|-------------|-----------|-------------------|------------------------|
| PIN COUNT | GENDER | PLUG BODY | CABLE TYPE & SIZE | PRODUCT DESCRIPTION |
| 3 Pin | Male/Female | Straight | PVC TC-ER/10 AWG | GSDA GKDA 30-2M/S4000 |
| | | | | GSDA GKDA 30-5M/S4000 |
| | | | | GSDA GKDA 30-10M/S4000 |
| 4 Pin | Male/Female | Straight | PVC TC-ER/10 AWG | GSDA GKDA 40-2M/S4000 |
| | | | | GSDA GKDA 40-5M/S4000 |
| | | | | GSDA GKDA 40-10M/S4000 |

D-SIZE Powerfast

IN-STOCK PROGRAM

D-Size Powerfast



| RECEPTACLES | | | |
|-------------|--------|-------------------------|-------------------------|
| PIN COUNT | GENDER | MOUNTING STYLE | PRODUCT DESCRIPTION |
| 3 Pin | Male | 1/2" NPT | GSDFA 30-0.5M/14.5/NPT |
| | | | GSDFA 30-2M/14.5/NPT |
| | | 3/4"NPT | GSDFA 30-0.5M/14.75/NPT |
| | | | GSDFA 30-2M/14.75/NPT |
| | Female | 1/2" NPT | GKDFA 30-0.5M/14.5/NPT |
| | | | GKDFA 30-2M/14.5/NPT |
| 3/4"NPT | | GKDFA 30-0.5M/14.75/NPT | |
| | | GKDFA 30-2M/14.75/NPT | |
| 4 Pin | Male | 1/2" NPT | GSDFA 40-0.5M/14.5/NPT |
| | | | GSDFA 40-2M/14.5/NPT |
| | | 3/4"NPT | GSDFA 40-0.5M/14.75/NPT |
| | | | GSDFA 40-2M/14.75/NPT |
| | Female | 1/2" NPT | GKDFA 40-0.5M/14.5/NPT |
| | | | GKDFA 40-2M/14.5/NPT |
| | | 3/4"NPT | GKDFA 40-0.5M/14.75/NPT |
| | | | GKDFA 40-2M/14.75/NPT |



| TEES | | |
|-----------|--------------|---------------------|
| PIN COUNT | DROP STYLE | PRODUCT DESCRIPTION |
| 3 Pin | D-Size Power | GSDA/2GKDA 30 |
| | A-Size Power | GSDA/GKDA/RKM 34 |
| 4 Pin | D-Size Power | GSDA/2GKDA 40 |
| | A-Size Power | GSDA/GKDA/RKM 44 |



| FIELD WIREABLES | | | |
|-----------------|--------|-----------|---------------------|
| PIN COUNT | GENDER | PLUG BODY | PRODUCT DESCRIPTION |
| 3 Pin | Male | Straight | GSDA 30-0 |
| | Female | Straight | GKDA 30-0 |
| 4 Pin | Male | Straight | GSDA 40-0 |
| | Female | Straight | GKDA 40-0 |

D-SIZE Powerfast

IN-STOCK PROGRAM

Notes:

Notes:

Notes:

CONNECTIVITY IN-STOCK PROGRAM


Turck sells its products through Authorized Distributors. These distributors provide our customers with technical support, service and local stock. Turck distributors are located nationwide – including all major metropolitan marketing areas.

For Application Assistance or for the location of your nearest Turck distributor, call:
1-800-544-7769

Specifications in this manual are subject to change with out notice. Turck also reserves the right to make modifications and makes no guarantee of the accuracy of the information contained herein.

Literature and Media questions or concerns?
Contact Marketing Communications Turck USA – media@turck.com

TURCK



28 subsidiaries and over
60 representations worldwide!

Printed in USA

©2015 by Turck Inc. All rights reserved. No part of the
publication may be reproduced without written permission.

B2404 B 11/15

www.turck.com